



Art.no. **6700**

Manual diesel dispensing nozzle, body in aluminium, with plastic hose tail \varnothing 25 mm and dispensing outlet with \varnothing ext. 25 mm, with latch for locking of trigger.

Max flow rate 90 l/min.

The nozzle can also be used for the dispensing of oils with a max. pressure of 7 bar.

Art.no. **6701**

Same as art. no. 6700, but with inlet swivel 1" BSP (M-F).



Art.no. **6725**

Automatic shut-off dispensing nozzle for diesel, body in aluminium with rubber protection, with inlet swivel 1" BSP (M-F) and dispensing outlet with \varnothing ext. 24 mm.

Max flow rate 60 l/min.



Art.no. **6726**

Automatic shut-off dispensing nozzle for diesel, body in aluminium with rubber protection, with inlet swivel 1" BSP (M-F) and dispensing outlet with \varnothing ext. 29 mm.

Max flow rate 110 l/min.



Art.no. **6721**

Automatic shut-off dispensing nozzle for diesel, high delivery version, body in aluminium, with inlet swivel 1 1/2" BSP (M-F) and dispensing outlet with \varnothing ext. 39 mm, with latch for locking of trigger.

Max flow rate 280 l/min.



Art.no. **2107/34**

Inlet swivel 3/4" BSP (M) – 1" BSP (F).

Art.no. **2107/33**

Inlet swivel 3/4" BSP (M) – 3/4" BSP (M).

Art.no. **2107/10**

Inlet swivel 1" BSP (M) – 1" BSP (F).

Art.no. **2107/35**

Inlet swivel 3/4" BSP (M) – 1" BSP (M).

Art.no. **2107/36**

Inlet swivel 1" BSP (M) – 1" BSP (M).



Art.no. **6439/2P**

Suction hose assembly for diesel pumps and transfer kits, composed of blue PVC – hose, length 2 m, \varnothing int. 25 mm, with 2 suitable hose tails with connection 1" BSP (M), 2 suitable hose clamps and suction non-return foot valve, body in brass, with filter in stainless steel, connection 1" BSP (F).