



| Codice Code | K | Z | kg | E BSP | L | L1 | C | ØT | Codice Code | K | Z | kg |
|---------------------------|-----|-----|---------------------------|-----------------|-----|-----|------|---------------------------|-----------------|-----|-----|-------|
| ØD 48 ØAL 40 ØS 20 | | | ØD 48 ØAL 40 ØS 25 | | | | | | | | | |
| HMOLM0400200100 | 100 | 195 | 1,75 | 1/4" | 32 | 20 | 12 | 50 | HMOLM0400250100 | 100 | 195 | 1,90 |
| HMOLM0400200150 | 150 | 245 | 2,09 | | | | | | HMOLM0400250150 | 150 | 245 | 2,31 |
| HMOLM0400200200 | 200 | 295 | 2,43 | | | | | | HMOLM0400250200 | 200 | 295 | 2,72 |
| HMOLM0400200250 | 250 | 345 | 2,76 | | | | | | HMOLM0400250250 | 250 | 345 | 3,14 |
| HMOLM0400200300 | 300 | 395 | 3,09 | | | | | | HMOLM0400250300 | 300 | 395 | 3,53 |
| HMOLM0400200400 | 400 | 495 | 3,78 | | | | | | HMOLM0400250400 | 400 | 495 | 4,35 |
| HMOLM0400200500 | 500 | 595 | 4,46 | HMOLM0400250500 | 500 | 595 | 5,17 | ØD 58 ØAL 50 ØS 30 | | | | |
| ØD 58 ØAL 50 ØS 25 | | | ØD 58 ØAL 50 ØS 30 | | | | | | | | | |
| HMOLM0500250100 | 100 | 205 | 2,60 | 3/8" | 36 | 22 | 13 | 60 | HMOLM0500300100 | 100 | 205 | 2,78 |
| HMOLM0500250150 | 150 | 255 | 3,06 | | | | | | HMOLM0500300150 | 150 | 255 | 3,32 |
| HMOLM0500250200 | 200 | 305 | 3,52 | | | | | | HMOLM0500300200 | 200 | 305 | 3,87 |
| HMOLM0500250250 | 250 | 355 | 3,97 | | | | | | HMOLM0500300250 | 250 | 355 | 4,41 |
| HMOLM0500250300 | 300 | 405 | 4,43 | | | | | | HMOLM0500300300 | 300 | 405 | 4,95 |
| HMOLM0500250400 | 400 | 505 | 5,34 | | | | | | HMOLM0500300400 | 400 | 505 | 6,03 |
| HMOLM0500250500 | 500 | 605 | 6,27 | HMOLM0500300500 | 500 | 605 | 7,12 | ØD 68 ØAL 60 ØS 30 | | | | |
| ØD 68 ØAL 60 ØS 30 | | | ØD 68 ØAL 60 ØS 35 | | | | | | | | | |
| HMOLM0600300100 | 100 | 220 | 3,77 | 3/8" | 39 | 25 | 13 | 70 | HMOLM0600350100 | 100 | 220 | 3,99 |
| HMOLM0600300150 | 150 | 270 | 4,36 | | | | | | HMOLM0600350150 | 150 | 270 | 4,68 |
| HMOLM0600300200 | 200 | 320 | 4,95 | | | | | | HMOLM0600350200 | 200 | 320 | 5,37 |
| HMOLM0600300250 | 250 | 370 | 5,54 | | | | | | HMOLM0600350250 | 250 | 370 | 6,06 |
| HMOLM0600300300 | 300 | 420 | 6,13 | | | | | | HMOLM0600350300 | 300 | 420 | 6,75 |
| HMOLM0600300400 | 400 | 520 | 7,32 | | | | | | HMOLM0600350400 | 400 | 520 | 8,14 |
| HMOLM0600300500 | 500 | 620 | 8,50 | HMOLM0600350500 | 500 | 620 | 9,52 | ØD 78 ØAL 70 ØS 35 | | | | |
| ØD 78 ØAL 70 ØS 35 | | | ØD 78 ØAL 70 ØS 40 | | | | | | | | | |
| HMOLM0700350100 | 100 | 220 | 4,82 | 3/8" | 39 | 25 | 13 | 80 | HMOLM0700400200 | 200 | 320 | 6,79 |
| HMOLM0700350150 | 150 | 270 | 5,56 | | | | | | HMOLM0700400250 | 250 | 370 | 7,64 |
| HMOLM0700350200 | 200 | 320 | 6,30 | | | | | | HMOLM0700400300 | 300 | 420 | 8,50 |
| HMOLM0700350250 | 250 | 370 | 7,04 | | | | | | HMOLM0700400400 | 400 | 520 | 10,21 |
| HMOLM0700350300 | 300 | 420 | 7,80 | | | | | | HMOLM0700400500 | 500 | 620 | 11,94 |
| HMOLM0700350400 | 400 | 520 | 9,27 | | | | | | | | | |
| HMOLM0700350500 | 500 | 620 | 10,76 | | | | | | | | | |

MATERIALE TUBO: ACCIAIO S1 52.3 DIN 2393 ISO H9
TUBE MATERIAL : STEEL S1 52.3 DIN 2393 ISO H9

MATERIALE ASTA: ACCIAIO UNI C45 SAE 1045 CROMO 25 µm ±5 Rating 9 / 200h ISO 10289 - 1999/ISO 9227-NSS
ROD MATERIAL : STEEL UNI C45 SAE 1045 CHROME 25 µm ±5 Rating 9 / 200h ISO 10289 - 1999/ISO 9227-NSS

CARATTERISTICHE TECNICHE : VEDI PAGINA 30 - TECHNICAL SPECIFICATIONS : SEE PAGE 30



www.hydrotruck.cz
info@hydrotruck.cz

Hydrotruck s.r.o.
Tovačovská 3457/4a
750 02, Přerov
Česká republika